

Description

Carbon monoxide detector E703H-2 is part of the gas detector family for industrial and tertiary use. The detector has a head with an electrochemical cell that measure toxic gas concentration on ppm scale (parts per million). The detector is pre-set with prewarning level at 100 ppm and warning level at 200 ppm. Oxygen detectors E710H-2 and E711H-2 are provided with a head with an electrochemical cell that measure oxygen volume percentages. Detectors are pre-set with prewarning level at 24% Vol. warning at 27% Vol. for the E710H-2, and prewarning at 18% vol and warning at 15% Vol. for the E711H-2. A handheld programmer and a PC software are optionally available; with them it is possible to conduct a field test of the detector and to change the configuration: detection treshold, alarm filters, addressing, full scale, etc. Head replacement can be done only by manufacturer. The detector is supplied with explosion-proof metal case unit with ATEX II 2G Ex-d IIC T6 certification for the location of the electronic communication and of the sensitive element, that is placed into the lower part and protected by a sintered filter in resined steel enclosure.

Models

MOON serie gas detectors are provided with two electronic boards; one for calibration algorithm control and sensitive element compensation (1), a second one to manage communication towards controlling system (2).


The detector comes with one of the following communication cards:

-42 Analogue output model of 4-20 mA, both active and passive, positive or negative. Typical connection for application with PLC. Possibility of calibrating the full scale signal values.

-RL 3 Relay output module for Prewarning and Warning. Dry contact outputs can be set as NA or NC, normally used for the connection in brglary systems or directly used for electrical boards.

-LV Communication module for analogue boards with Teledata protocol. The module can trasmit prewarning, warning and fault information using a single Loop address (depending on the central system). Up to 240 detectros for Loop.

G7-BASE-2 CARD



HELPCARD

Rilevamenti

E55503XX	Monossido di carbonio
E55510XX	Ossigeno Eccesso
E55511XX	Ossigeno Difetto



Technical data

Supply voltage	12/24 Vdc
Sensitive element	Catalytic
Power consumption in stand-by	40 mA max
Power consumption in alarm	50 mA max
Operating temperature	0°C / +40 °C
Relative humidity	90%
Enclosure	ATEX ADPE
Weight	1000 g
Dimension (HxWxD)	165x90x80
Ø Screw	1" GAS
ATEX II 2G Ex-d IIC T6 Certified	