

## Description

---

**ONEPRINTER** is an RS232C serial thermal printer supplied in a wall box designed to be connected to the Teledata series of fire control panels.

**ONEPRINTER** is programmed from the web using a simple interface, prints all events and all the commands of the control units connected to it.

**ONEPRINTER** performs the gateway functionality allowing centralization through CEI ABI protocol

**ONEPRINTER** is built with a metal case made of iron sheet 10/10 powder coated.



## Features

---

- Low-noise direct thermal printing method
- Fast printing speed, low noise
- Can support Max.39mm (diameter) paper roll.
- Easy paper loading structure

## General Specifications

---

| ITEM                  | SPECIFICATION                |
|-----------------------|------------------------------|
| Print method          | Thermal direct line printing |
| Paper width           | 58mm                         |
| Print width           | 48mm                         |
| Resolution ration     | 8dots/mm(384dots/line)       |
| Life of printing head | 50km                         |
| Printing speed        | 60mm/sec                     |
| Character size        | ANK:9x17,12x24;GBK:24x24     |
| Interface             | RS232C                       |
| Input power           | 24Vcc                        |
| Operating temperature | 5°C-50°C                     |
| Storage temperature   | -20°C-60°C                   |
| Operating umidity     | 10°C-80°C                    |
| Storage umidity       | 10°C-90°C                    |
| Dimension             | 160x124x108mm                |