




OPTICAL ACOUSTIC DISPLAY CONNECTION CABLAGGIO TARGA OTTICO ACUSTICA

TARGA OTTICO ACUSTICA mod. FD 5970

OPTICAL ACOUSTIC DISPLAY mod. FD 5970



CONNECTOR on CARD TD571
CONNETTORE su SCHEDA TD571



FIRE - Power supply lines

Power cable type: 24 Vdc shielded

Power supply cable chart: 27,6 Vcc

Maximum voltage drop: 4 Vcc with 1A current

- 1 mmq (34 ohm/Km) Max lenght: 117,6 Mt

- 1,5 mmq (22,5 ohm/Km) Max lenght: 177,7 Mt

- 2,5 mmq (14 ohm/Km) Max lenght: 285,7 Mt

FIRE - Linee di alimentazione

Linea alimentazione tipo: 24 Vdc schermato

Tabella per cavo alimentazione: 27,6 Vcc

Massima caduta di tensione consentita: 4 Vcc

Con una corrente di 1A

- 1 mmq (34 ohm/Km) Dist Max: 117,6 Mt

- 1,5 mmq (22,5 ohm/Km) Dist Max: 177,7 Mt

- 2,5 mmq (14 ohm/Km) Dist Max: 285,7 Mt

twisted and shielded cable with two wires
cavo twistato e schermato a due conduttori
LSZH GR4 EN50200 CE120-36/20-37

da dispositivi su loop
from other devices on loop

Loop +
Loop -

Distances with detectors, modules I/O or call points (max 240 for loop)

- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq

For addressable sounder or wireless receivers the distance depends on the quantity of devices.



TELEDATA®



MOD. ONE



mod. FD 5970/2

N°031
FAMILY: FIRE SYSTEM
Tel. +39 02-2592795 +39 02-27201352 Fax +39 02-2593704

TYPE: ACOUSTIC OPTICAL DISPLAY PANELS
Per sirene indirizzate o ricevitori via radio la distanza viene dimensionata in funzione del numero di dispositivi.