



# FIRE ALARM CONVENTIONAL BEACON CONNECTION CABLAGGIO BEACON CONVENZIONALE



CONNECTOR on CARD TD571  
CONNETTORE SU SCHEMA TD571

O 01 PS2+
O 02 PS2-
O 03 PS1+
O 04 PS1-
O 05 BATT-
O 06 BATT+
O 07 DIM+
O 08 DIM-
O 09 FW+
O 10 FW-
O 11 RET+
O 12 RET-
O 13 RS485+
O 14 RS485+
O 15 GND
O 16 PSOUT
O 17 SIR+
O 18 SIR-
O 19 AL(guasto)
O 20 AL(guasto)



Distances with detectors, modules I/O or call points (max 240 for loop)	Distanze con sensori, moduli I/O o pulsanti (max 240 per loop)	
- 1250 mt. 2x0,5 mmq	- 1250 mt. 2x0,5 mmq	
- 1850 mt. 2x0,75 mmq	- 1850 mt. 2x0,75 mmq	
- 2500 mt. 2x1 mmq	- 2500 mt. 2x1 mmq	
- 3500 mt. 2x1,5 mmq	- 3500 mt. 2x1,5 mmq	
- 5000 mt. 2x2,5 mmq	- 5000 mt. 2x2,5 mmq	
For addressable sounder or wireless receivers the distance depends on the quantity of devices.	Per sirene indirizzate o ricevitori via radio la distanza viene dimensionata in funzione del numero di dispositivi.	N°xxx_at FAMILY: FIRE SYSTEM TYPE: SIRENS AND BELLS