


SIREN FOR FIRE DETECTORS CONNECTION

CABLAGGIO SIRENA PER RILEVATORE ANTINCENDIO

ADDRESSABLE 32 TONE SIREN FOR FIRE DETECTORS
SIRENA INDIRIZZATA PER RILEVATORE ANTINCENDIO
mod. 40200

mod. 40200 +33330


SIREN FOR FIRE DETECTORS WITH
OPTICAL REMOTE
SIRENA PER RILEVATORE ANTINCENDIO
CON RIPETTORE OTTICO
mod. 40200 +33330



CONNECTOR on CARD TD571
CONNETTORE su SCHEDA TD571

twisted and shielded cable with two wires
cavo twistato e schermato a due conduttori
da dispositivi sul loop
from other devices on loop

LSZH GR4 EN50200 CEI20-36/20-37



FDF110


twisted and shielded cable with two wires

cavo twistato e schermato a due conduttori

Distances with detectors, modules I/O or call points (max 240 for loop)

- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq

For addressable sounder or wireless receivers the distance depends on the quantity of devices.



MOD. ONE

mod. 40200

20132 MILANO - Via Giulietti, 8

Tel. +39 02-2592795 +39 02-27201352 Fax +39 02-2593704

FAMILY: FIRE SYSTEM TYPE: ACCESSORIES FOR ADDRESSED DETECTORS