



# FLOOD PROTECTION DETECTOR CONNECTION

## CABLAGGIO RILEVATORE ANTIALLAGAMENTO




CONNECTOR on CARD TD571  
CONNETTORE su SCHEDA TD571



da dispositivi su loop  
from other devices on loop

twisted and shielded cable with two wires  
cavo twistato e schermato a due conduttori  
LSZH GR4 EN50200 CEI20-36/20-37



- |                     |                |
|---------------------|----------------|
| 1 cavo color rosso  | 1 red cable    |
| 2 cavo color nero   | 2 black cable  |
| 3 cavo color giallo | 3 yellow cable |
| 4 cavo color bianco | 4 white cable  |

Distances with detectors, modules I/O or call points (max 240 for loop)

- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq

For addressable sounder or wireless receivers the distance depends on the quantity of devices.

Distanze con sensori, moduli I/O o pulsanti (max 240 per loop)

- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq

Per sirene indirizzate o ricevitori via radio la distanza viene dimensionata in funzione del numero di dispositivi.

MOD. ONE	mod. FD 2450
N°039_a	
FAMILY: FIRE SYSTEM	TYPE: ACOUSTIC OPTICAL DISPLAY PANELS

TELEDATA®  
20132 MILANO - Via Giulietti, 8  
Tel. +39 02-2592795 +39 02-27201352 Fax +39 02-2593704