


OPTICAL/THERMAL DETECTOR BASE CONNECTION

COLLEGAMENTO BASI RIVELATORI OTTICI/TERMICI




CONNECTOR on CARD TD571
CONNETTORE su SCHEDA TD571

○ 01	PS2+
○ 02	PS2-
○ 03	PS1+
○ 04	PS1-
○ 05	BATT-
○ 06	BATT+
○ 07	DIM+
○ 08	DIM-
○ 09	FW+
○ 10	FW-
○ 11	RET+
○ 12	RET-
○ 13	RS485-
○ 14	RS485+
○ 15	GND
○ 16	PSOUT
○ 17	SIR+
○ 18	SIR-
○ 19	AL(guasto)
○ 20	AL(guasto)

da dispositivi su loop
from other devices on loop

twisted and shielded cable with two wires
cavo twistato e schermato a due conduttori
LSZH GR4 EN50200 CEI20-36/20-37



Distances with detectors, modules I/O or call points (max 240 for loop)


- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq

For addressable sounder or wireless receivers the distance depends on the quantity of devices.

Distanze con sensori, moduli I/O o pulsanti (max 240 per loop)

- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq

Per sirene indirizzate o ricevitori via radio la distanza viene dimensionata in funzione del numero di dispositivi.




MOD. ONE

mod. SF5100/SF5200

SF5300/SF5100E

SF5200E/SF5300E



TELEDATA®

20132 MILANO - Via Giulietti, 8

Tel. +39 02-2592795 +39 02-27201352 Fax +39 02-2593704

N°001_at FAMILY: FIRE SYSTEM TYPE: ADDRESSABLE DETECTORS