


ELECTROMAGNETIC BLOCK CONNECTION

CABLAGGIO FERMI ELETTRONICI



CONNECTOR on CARD TD571
CONNETTORE su SCHEDA TD571




twisted and shielded cable with two wires
cavo twistato e schermato a due conduttori

LSZH GR4 EN50200 CEI20-36/20-37

Distances with detectors, modules I/O or call points (max 240 for loop)

- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq


For addressable sounder or wireless receivers the distance depends on the quantity of devices.



Distanze con sensori, moduli I/O o pulsanti (max 240 per loop)

- 1250 mt. 2x0,5 mmq
- 1850 mt. 2x0,75 mmq
- 2500 mt. 2x1 mmq
- 3500 mt. 2x1,5 mmq
- 5000 mt. 2x2,5 mmq


Per sirene indirizzate o ricevitori via radio la distanza viene dimensionata in funzione del numero di dispositivi.



MOD. ONE

mod. FDM5411E-F

mod. FDM9412E



TELEDATA®

20132 MILANO - Via Giulietti, 8

Tel. +39 02-2592795 +39 02-27201352 Fax +39 02-2593704

N°055_a FAMILY: FIRE SYSTEM

TYPE: ELECTROMAGNETIC BLOCK